

## **DRILL-X™ HP**

## **Product Information**

Description

New and Improved, High Performance **DRILL-X**<sup>™</sup> **HP** is a thinning drilling detergent and wetting agent for use in fresh water drilling fluid systems where clays are present. **DRILL-X**<sup>™</sup> **HP** can be added to fluids to keep bits and tooling clean and adding lubrication properties to the system. **DRILL-X**<sup>™</sup> **HP** also acts as a secondary thinner to lower fluid viscosity and aid in dispersing clays. When drilling through clays, additions of **DRILL-X**<sup>™</sup> **HP** will assist in making clays more flowable and preventing cuttings from sticking together.

Characteristics

**DRILL-X**<sup>™</sup> **HP** is environmentally safe, non-toxic, and biodegradable.

- Reddish Color liquid
- Pour point >30° F
- Safe and non-toxic
- Bulk density –8.4 lbs/gal
- Flash point -210° F

To keep from freezing store above 30° F.

Application

Addition/500 Gallons of Drilling Fluid

For Lubrication and Bit Cleaning 3 to 4 Quarts
To Disperse Clays / Improve Fluid Loss 4 to 5 Quarts

**Packaging** 

**DRILL-X**<sup>™</sup> **HP** is available in 5 gallon pails and 53 gallon drums.